

Power Distribution Unit



Make - **FIRSTOUCH**

Model No. **FTDPDUA04**

Serial No. **FTD1736KPDU12062601**

Power Distribution Unit	Front Door	2 Hinges with Rack
	Wall Mount Clamp	Welded on Rack frame rear side
	19" pillar front & 19" pillar rear	Bolted on rack side wall
	Locking Arrangement	Provided with a locking system
	Limit Switch	The rack door provided with a limit switch
	Earthing	Earthing studs are be provided in the rack for Earthing purposes
	Cable points	Cable entry and exit points are provided in the rack
	Mounting	Mount the rack either on a pole or on a wall with options of different mounting types
	Material	GI 120 gsm thickness 1.5 mm
	IP rating	IP55
	AC input	220-240VAC
	Nominal Input Voltage	100-120 VAC
	Input Frequency	50-60 Hz
	AC Power Load Max	As per LED power requirement
	Surge protection	Class C
	Over temperature protection	Selectable from 30 deg to 60 deg C
	Refrigerant	R134a for harsh conditions
	Anti-Theft	Mounted in an ant-theft design
	Surface treatment	Outdoor type power coating
	Cooling Capacity	Minimum 600W@L35/L35
	Power Consumption	Maximum 270W@L35/L35
	Internal Airflow	Minimum 150 m ³ /
	Maximum Noise Level	65 dB(A)s
	Remote Control	Control the power distribution unit from the Central Control Center over IP
Display Panel	Provided with a display panel to show parameters like cabinet temperature, indications for - cooling, running of external fans, flashing on alarm	